



DOOR PRODUCTS REPAIR & RETURN POLICY

WARRANTY REPAIRS:

Warranties cover parts and workmanship provided by MS SEDCO. Repair warranties are void if units are altered by anyone other than the MS SEDCO Repair Center. All warranties begin at invoice date unless specified by MS SEDCO. Customer will pay freight charges to return defective units to MS SEDCO Repair Center. Units will be repaired to proper working order and returned in “cosmetically same” condition at no charge. MS SEDCO will pay freight charges to ship repaired warranty units back to customer. **

OUT OF WARRANTY REPAIRS:

All units out of warranty that are returned for repair will be charged under the MS SEDCO repair rates shown below. Units will be repaired to proper working order and returned in “cosmetically same” condition. All units exceeding 5 years over warranty period will be scrapped on site, or returned to customer (at customers freight cost) unrepaired.

ADVANCE EXCHANGE PROGRAM:

MS SEDCO Repair Center advance exchange program allows you to receive refurbished units quickly. Shipping and handling charges are extra. Please send your malfunctioning unit to us within 10 days to avoid up-charges. Up-charges also apply if the unit MS SEDCO receives is not repairable due to excessive damage or an incorrect model. Up-charges are generally assessed as the difference between the repair price and the new product price. All warranties on exchanges are subject to the same standard terms and conditions as a repaired unit. Advanced exchange units must be returned with all accessories (brackets, transformers, harnesses, manuals) or will be charged per non-returned accessories.

ADVANCE EXCHANGE RETURN POLICY:

MS SEDCO Repair Center accepts returns on advance exchange units. All advanced exchange units must be returned within 10 days of the original exchange order. Items may be assessed a 15% restocking fee and all applicable shipping and COD charges will apply. Advanced exchanged units must be returned in original packaging. Damaged units will not be accepted for exchange credit. Please contact customer service to receive authorization for the return before shipping it to MS SEDCO. MS SEDCO will only issue credits for returned units not refunds.

TURNAROUND TIME:

MS SEDCO Repair Center turnaround time typically requires 72~96 hours plus shipping on all units.

EXPEDITING ORDERS:

Some orders can be repaired in 24 hours for an additional charge. Call to see if your order qualifies. Expedited orders are charged at 30% above the repair price.

PAYMENT TERMS:

Payment is required prior to shipping unless a credit application has been received and accepted by MS SEDCO. Repaired units will be detained if customer is on credit hold with MS SEDCO billing department. Detained units will be returned after credit hold has been lifted from MS SEDCO billing department. Repairs can be billed by credit card for non net 30 day customers.

RETURN SHIPPING:

All repairs are returned via ground service. For an additional charge, guaranteed overnight service is also available. Customers are responsible for all shipping, customs and insurance costs on out of warranty repairs and express units. When possible, we will ship via your requested carrier.

MS SEDCO REPAIR RATE:

Door Sensors	\$70.00 (Pedestrian)
	\$120.00 (Industrial)
Door Accessories	\$40.00

Rates do not include freight and are subject to change without notice.

EVALUATIONS:

MS SEDCO Repair Center will evaluate certain units for reparability at no charge. If you have an item requiring repair, please contact us to see if it qualifies for a free repair evaluation.

**UNREPAIRED UNITS:

MS SEDCO reserves the right not to repair any units that have excessive damage, missing parts, or for which parts are currently unavailable. Unrepaired items will be returned with billed shipping charges, or scraped on site at no charge.

RETURN FOR CREDIT

1. All items being returned for CREDIT must have an MS SEDCO original invoice number included with the items to ensure proper credit.

a. **Unused and unopened items** will be issued full credit if returned within 30 days. A 15% restocking fee will be assessed on items returned after 30 days past invoice date. No credit will be issued after 6 months past invoice date.

b. **Unused but opened items** will be assessed a 15% restocking charge if returned within 30 days of invoice date and it is determined the items can be resold as new. If it is determined that the items cannot be resold as new, the items will be returned or scrapped at the customer's discretion. No credits will be issued after 30 days past invoice date.

c. **Used items** cannot be returned for credit.

d. **Custom Products** cannot be returned for credit.
2. In the event items are being returned due to an error on MS SEDCO part, MS SEDCO will issue a call tag and pay freight charges for returned items. The customer will pay freight charges on all returns for any other reason.
3. MS SEDCO will only issue credit for returned items—not refunds.
4. No credits will be issued for products with missing serial numbers.



ENGINEERED FOR MOTION

2018 RETAIL PRICE LIST

Pages 1–2	SafePath™ Door Activation & Safety Sensor Products 
Pages 2–8	Sedco™ Door Activation Switch Products, Bollards
Pages 8–10	 Radio Control Products
Pages 10-11	 2.4 GHz Radio Control Products
Page 11-12	AccuGuard™ Safety Beams
Page 12	Door Decals
Page 13	 The Commander Series™ Timing Controls
Page 14	Guide Rails & Bumper Guards
Page 15	Door Products Repair & Return Policy



Free Shipping on all Door Product orders over \$2500
See Website for Details





RETAIL PRICE LIST 2018

PART #	DESCRIPTION	RETAIL PRICE
SafePath™ Door Activation & Safety Sensor Products S.A.F.E. SafePath™ Automation For Entrances		
Microwave Sensors		
microStar-M		225
	Microwave Motion Sensor w/Human Presence Radar™ (HPR™) for activating all types of automatic doors. Unparalleled motion detection protects slow moving pedestrians from doors closing prematurely. • Fits 1 3/4” door frames • Visible LEDs to verify activation • Install mode lets pattern be set without cycling doors • HPR™ provides additional level of motion protection after initial door activation • Adjustable Unidirectional & Bi-directional • Narrow & Wide Pattern Antennas • Dual Axis Angle Adjustment	
microStar Accessories		
MS-BDB	Universal mounting bracket for microStar.	25
MSRC	Rain cover.	40
ID20		625
	Long-Range Microwave Motion Sensor for activating industrial doors. • Provides motion detection for vehicles and equipment up to 60 ft. away • Sealed aluminum, weather proof housing • Selectable Approach-only or Depart-only detection reduces unwanted door openings	
HR-Robus		308
	High mount Microwave Motion Sensor for activating industrial or pedestrian doors. • Provides motion detection for vehicles and/or pedestrian traffic • Two outputs selectable for pedestrian detection, vehicle detection, or both • Maximum installation height of 23 feet • Selectable Bi-directional, Approach-only or Depart-only detection reduces unwanted door openings	
HR-Robus Accessories		
Robus-RC	Remote control for programming and control of HR-Robus.	200
Infrared Sensors		
DH400		340
	Floor Reflection Method Active Infrared Presence Sensor. Provides safety protection for all types of automatic pedestrian doors. • One sensor covers safety zone application (single or pair: swing, slide, fold) • 5 rows of 12 points per row provide up to 60 detection zones for a dense safety pattern • Adjustable pattern width and depth	
DH94		250
	Floor Reflection Method Active Infrared Presence Sensor. Provides safety protection for automatic pedestrian sliding doors with shallow approaches. • 4 rows of 32 individual detection zones provides a dense safety pattern • Adjustable pattern width and depth	

RETAIL PRICE LIST 2018

PART #	DESCRIPTION	RETAIL PRICE	RETAIL PRICE
Guide Rails & Bumper Guard Products		Clear/Silver	Bronze
Guide Rails			
Guide rails are constructed of 6063-T6 aluminum alloy, rectangular in shape (1-3/4” wide by ½” thick), and available in clear anodized or dark bronze finish (specify –CL or –BR when ordering). Other rails available, including stainless and custom rails (contact factory).			
Double Line Wall-Mounted			
36 x 30	DLW-A	163	173
36 x 36	DLW-B	166	176
42 x 30	DLW-C	170	180
42 x 36	DLW-D	175	185
48 x 30	DLW-E	180	190
48 x 36	DLW-F	185	195
Double Line “I Brace” Wall-Mounted			
36 x 30	DLIW-A	185	195
36 x 36	DLIW-B	190	200
42 x 30	DLIW-C	195	205
42 x 36	DLIW-D	200	210
48 x 30	DLIW-E	205	215
48 x 36	DLIW-F	210	220
Double Line “I Brace” Free-Standing			
36 x 30	DLIF-A	235	245
36 x 36	DLIF-B	240	250
42 x 30	DLIF-C	245	255
42 x 36	DLIF-D	250	260
48 x 30	DLIF-E	257	267
48 x 36	DLIF-F	265	275
Horizontal Holding Beam Wall-Mounted			
42 x 30	HOW-C	290	315
42 x 36	HOW-D	298	323
48 x 30	HOW-E	306	331
48 x 36	HOW-F	314	339
Push Button Equipped Wall-Mounted			
42 x 30	PBOW-C	365	377
42 x 36	PBOW-D	370	382
48 x 30	PBOW-E	379	391
48 x 36	PBOW-F	388	400
Push Plate Switch-Ready Wall-Mounted			
36 x 42	HAOW-A	413	463
42 x 42	HAOW-B	419	469
48 x 42	HAOW-C	425	475
60 x 42	HAOW-D	725	775
72 x 42	HAOW-E	800	850
Bumper Guard			
Replacement Boot			
Face-Applied Finger Guard			
Center-Hung Finger Guard			
ALBG-A (30-44” Available - specify width when ordering)		105	110
TSMB		35	40
FAFG		88	88
			(black)
7’	CHFG-A	50	
8’	CHFG-B	66	
10’	CHFG-C	88	


RETAIL PRICE LIST 2018

PART #	DESCRIPTION	RETAIL PRICE
 The Commander Series Timing Controls & Lock Out Modules		
TDM Time Delay Module		95
	Universal Time Delay Module provides up to 4 inputs that can be converted to sequential relay outputs. Each output is adjustable 0-99 seconds. The TDM can add additional time of 0-99 seconds, sequence electric locks and automatic doors or sequence vestibule doors all from a single device.	
TDM-HC High-Current Time Delay Module		190
	TDM with the output 1 relay rated for a current inrush of 20 amps, making the TDM-HC compatible with all common locking devices.	
RLM-Kit		225
	Integrated Relay Lockout Module with Safety Beams. Intelligent Door Position™ Monitoring Circuitry determines relay lockout time during a door's closing cycle, eliminating the need for trial and error manual adjustment. Provides single source control of approach sensor, overhead safety sensor and safety beams installed on swing door operators.	
RLM Components		
RLM		105
RLM Control Module ONLY		
RLM-SB		130
1 set TX & RX Sensor Heads with 15' cables.		
SAM Secondary Activation Module		120
	Integrated Timing Module to meet secondary activation requirements of Knowing Act Swing Doors. Intelligent Door Position™ Monitoring circuitry determines the timing for turning on and off an approach sensor after initial door activation by a push plate while simultaneously monitoring the overhead safety sensor and locking out its signal during a door's closing cycle. Provides single source control of push plate, approach (secondary activation) sensor and overhead safety sensor.	
PTM Privacy Timing Module		
	The PTM is a timing module that allows users to control an automatic door operator for a room where privacy is a concern, such as a washroom, restroom, clean room, or photo development room. From the outside of the room, users are able to activate the door. Once inside, users are able to lock the door which prevents access from the outside "push to open" button. When egress is desired, the user presses an inside "push to open" button which deactivates the lock and activates the door. A keyswitch override is present on the exterior, as well as LEDs to indicate if the room is occupied.	
	PTM: (module and wire harness only) PTM-KIT: Includes module, wire harness, interior dual switch (59V-PTM), exterior combo switch (830B-59J-PTM), and door position switch.	159 405



RETAIL PRICE LIST 2018

PART #	DESCRIPTION	RETAIL PRICE
SafePath™ Door Activation & Safety Sensor Products (continued) 		
Infrared Combination Motion and Presence Sensors		
DH100-CT	 Floor Reflection Method Active Infrared Motion & Presence Sensor. Provides all-in-one door activation and safety for automatic pedestrian sliding doors. • 5 rows of 48 individual detection zones provides a dense rectangular pattern • Adjustable pattern width and depth	310
DHR3	 Combination Microwave Motion and Active Infrared Presence Sensor. Provides both activation and safety protection for automatic sliding and folding doors. • One sensor provides motion detection for door activation while simultaneously providing a dense safety pattern at the threshold of the door • 2 to 5 rows of Floor Reflection Method Presence Detection • Adjustable pattern width and depth	320
Infrared Sensor Accessories		
DH-BDB	Universal mounting bracket for DH400 & DHR3.	55
DH-MP	Mounting plate adapts the DH400 & DHR3 for attaching to 2" doorframes.	25
DHRC	Molded plastic rain cover for DH400, DH100, & DHR3.	40
Infrared Door Mounted Sensors		
SSS-5M1	 Active Infrared Presence Sensor with Position Sensitive Detection (PSD) technology provides precise safety protection within the path of any moving swing, bi-fold or revolving door panel • Easy dip switch set up • Adjustable detection angle, distance and width • Mounts at the top of the door out of harms way	
SSS-5M1: Sensor Module and 27 1/4" Housing		480
Sedco™ Door Activation Switch Products		
Switches include a hardware pack consisting of a water-resistant bellow, wire terminal connectors and tamper-proof screws.		
59 Series		62
	4 ½" Square Stainless Steel Switches. • 59-H: Blue Face Plate WHEELCHAIR/PRESS TO OPERATE DOOR • 59-HSS: Stainless Steel Face Plate WHEELCHAIR/PRESS TO OPERATE DOOR • 59-P: Stainless Steel Face Plate PRESS TO OPERATE DOOR • 59-W: Blue Face Plate WHEELCHAIR • 59-WSS: Stainless Steel Face Plate WHEELCHAIR • 59-PLAIN: Stainless Steel Face Plate NO LEGEND • 59-E-R: Red Face Plate PUSH TO EXIT Braille option available: 59-H-BRAILLE, 59-HSS-BRAILLE, 59-P-BRAILLE	72
59R4 Series		62
	4 ½" Round Stainless Steel Switches. • 59R4-H: Blue Face Plate WHEELCHAIR/PRESS TO OPERATE DOOR • 59R4-HSS: Stainless Steel Face Plate WHEELCHAIR/PRESS TO OPERATE DOOR • 59R4-P: Stainless Steel Face Plate PRESS TO OPERATE DOOR • 59R4-W: Blue Face Plate WHEELCHAIR • 59R4-WSS: Stainless Steel Face Plate WHEELCHAIR • 59R4-PLAIN: Stainless Steel Face Plate NO LEGEND	


RETAIL PRICE LIST 2018

PART #	DESCRIPTION	RETAIL PRICE
Sedco™ Door Activation Switch Products (continued)		
59R6 Series		75
	6" Round Stainless Steel Switches. • 59R6-H: Blue Face Plate WHEELCHAIR/PRESS TO OPERATE DOOR • 59R6-HSS: Stainless Steel Face Plate WHEELCHAIR/PRESS TO OPERATE DOOR • 59R6-P: Stainless Steel Face Plate PRESS TO OPERATE DOOR • 59R6-W: Blue Face Plate WHEELCHAIR • 59R6-WSS: Stainless Steel Face Plate WHEELCHAIR • 59R6-PLAIN: Stainless Steel Face Plate NO LEGEND	
59J Series		60
	1 11/16" x 4 1/2" Stainless Steel Jamb Switches. • 59J-H: Blue Face Plate WHEELCHAIR/PUSH TO OPEN • 59J-HSS: Stainless Steel Face Plate WHEELCHAIR/PUSH TO OPEN • 59J-P: Stainless Steel Face Plate PUSH TO OPEN • 59J-W: Blue Face Plate WHEELCHAIR • 59J-WSS: Stainless Steel Face Plate WHEELCHAIR • 59J-PLAIN: Stainless Steel Face Plate NO LEGEND • 59J-E-R: Red Face Plate PUSH TO EXIT	
59V Series		125
	Two 59J Series Jamb Switches are integrated onto a 4 1/2" stainless steel back plate for independent operation of two doors inside the vestibule. Mounts to a 2-gang electrical box. • 59V-H: 2 Blue Face Plates WHEELCHAIR/PUSH TO OPEN/ARROWS • 59V-HSS: 2 Stainless Steel Face Plates WHEELCHAIR/PUSH TO OPEN/ARROWS • 59V-P: 2 Stainless Steel Face Plates PUSH TO OPEN/ARROWS • 59V-W: 2 Blue Face Plates WHEELCHAIR/ARROWS • 59V-WSS: 2 Stainless Steel Face Plates WHEELCHAIR/ARROWS • 59V-PLAIN: 2 Stainless Steel Face Plates NO LEGEND	
614 Series: Extreme		95
	1" Diameter Red Piezo Button Switch is waterproof and built to withstand any environment. Patented piezo technology has no moving parts making this switch virtually indestructible. Includes WHEELCHAIR and PUSH TO OPEN self-sticking MYLAR decals. • 614-SS: 4 1/2" Square Stainless Steel Face Plate • 614-NSS: 1 11/16" x 4 1/2" Stainless Steel Face Plate	
Custom Legends	Customize your stainless switch face plates with a corporate logo or custom look (one color-black). • One-Time Set-Up Charge—Text Only Customization ADD: \$25 (not subject to discount) • One-Time Set-Up Charge—Logo/Graphics Customization ADD: \$120 (not subject to discount) • Custom Text/Graphics Upcharge Per Faceplate ADD:	5
Custom Finishes	ADD: US3, US4, US10, US10B, US32 finishes are available on most switches. Contact factory for more information.	125
425 Series: Economy		36
	1" Diameter Red or Black Button Switches and jamb style face plate. Includes WHEELCHAIR and PUSH TO OPEN self-sticking Mylar decals. • 425B-BLK: Black Button/Blue Face Plate • 425SS-BLK: Black Button/Stainless Steel Face Plate • 425B-RED: Red Button/Blue Face Plate • 425SS-RED: Red Button/Stainless Steel Face Plate	



RETAIL PRICE LIST 2018

PART #	DESCRIPTION	RETAIL PRICE		
AccuGuard™ Safety Beam Products (continued)				
Infrared Safety Beams				
GD11-GDB		150		
	Surface Mount Infrared Beam, 0' to 40'. (Pictured with included GDB Mounting Bracket)			
	GD11S (without GDB Mounting Bracket)	136		
GDB		35		
Heavy Duty Surface Mounting Bracket For GD11S Safety Beams.				
Door Safety Decals				
Two sided decals are depicted with opposite side partially shown.				
Door Decals: English		12		
MSS-1 Blue & White	MSS-2 Yellow & Black	MSS-3 Green, Black & White	MSS-4 Red, Black & White Green, Black & White	MSS-15 Yellow, Black & Blue
ACTIVATE SWITCH TO OPERATE				
MSS-13 Red & White				
STAND CLEAR				
MSS-5 White & Blue		MSS-6 Red & White		
		IN EMERGENCY PUSH TO OPEN		
Door Decals: English/Spanish		16		
MSS-7 Blue & White	MSS-8 Yellow & Black	MSS-9 Green, Black & White	MSS-10 Red, Black & White Green, Black & White	MSS-16 Yellow, Black & Blue
ACTIVATE SWITCH TO OPERATE ACTIVE EL INTERRUPTOR PARA OPERAR				
MSS-14 Red & White				
STAND CLEAR Mantengase a Distancia				
MSS-11 White & Blue		MSS-12 Red & White		
		IN EMERGENCY PUSH TO OPEN EN CASO DE EMERGENCIA PRESIONE PARA ABRIR		

RETAIL PRICE LIST 2018

PART #	DESCRIPTION	RETAIL PRICE
ClearPath Spectrum 2.4 GHz Radio Control Products (continued)		
S-TRX-VP: Dual Post Transceivers	Complete with 2 transceivers, wire harnesses, and batteries installed on a mounting platform that spans the top of the 608 Series Post assembly.	190
		
S-TRX-HH: Handheld Transceiver	1 button handheld transceiver that includes lanyard	120
		
S-COR: Spectrum Coordinator	ClearPath Spectrum Coordinator that functions similar to standard radio control receiver. LCD screen for easy programming. Features two way digital communication that provides enhanced security and reliable signal transmission between devices. Two built in outputs.	150
		
ClearPath™ Spectrum Kits		
Kits listed below include -H face plates. For -HSS face plates, substitute HSS for H in the part number below, for -P face plates, substitute P for H.		
Package 59	STK-H 2:59-H; 2:S-TRX; 1:S-COR	440
Package 59R4	STK-R4-H 2:59R4-H; 2:S-TRX-R4; 1:S-COR	440
Package 59R6	STK-R6-H 2:59R6-H; 2:S-TRX-R6; 1:S-COR	440
Package 59J	STK-J-H 2:59J-H; 2:S-TRX-J; 1:S-COR	440
Vestibule Package 59	STK-HV 2:59-H; 2:S-TRX; 1:59V-H; 1:S-TRX-V; 2:S-COR	850
Vestibule Package 59J	STK-J-HV 2:59J-H; 1:59V-H; 2:S-TRX-J; 1:S-TRX-V; 2:S-COR	850
NexGen CT Wireless HSS	STK-NGS-CT-HSS 2:NGS-CT-HSS; 1:S-COR	545
NexGen CT Wireless P	STK-NGS-CT-P 2:NGS-CT-P; 1:S-COR	545
NexGen IR Wireless	STK-NGS-IR-A 2:NGS-IR-A; 1:S-COR	545
NexGen IR/CT-HSS Wireless	STK-NGS-IR-A/CT-HSS 1:NGS-IR-A; 1:NGS-CT-HSS; 1:S-COR	545
NexGen IR/CT-P Wireless	STK-NGS-IR-A/CT-P 1:NGS-IR-A; 1:NGS-CT-P; 1:S-COR	545
AccuGuard™ Safety Beam Products		
Infrared Safety Beams		
AccuGuard HP2	Infrared modular beam system consists of one control module, 2 transmitter beams with cables and 2 receiver beams with cables.	155
		
AccuGuard HP2–Surface	HP2 Infrared modular beam system with 4 surface mount boxes for the sensor beam heads.	205
AccuGuard Components		
HP2-SMB	Surface mount box only for a sensor head.	15
DB11		
	Flush Mount Infrared Beam, 0' to 40'.	132
US DOLLARS—OCTOBER 2018 Prices are subject to change without notice. PAGE 11		


RETAIL PRICE LIST 2018

PART #	DESCRIPTION	RETAIL PRICE
Sedco™ Door Activation Switch Products (continued)		
1078 Series: Low Profile	4 ½" Square Stainless Steel Switch with 2" x 3" activating face plate that only projects ¼" from the wall.	90
	• 1078-H: Blue Face Plate WHEELCHAIR/PRESS TO OPERATE DOOR • 1078-P: Black Face Plate PRESS TO OPERATE DOOR • 1078-W: Blue Face Plate WHEELCHAIR	
216 Series: Infrared "Touchless"		
	Active Infrared Switch provides hands-free/germ-free door activation. Activation distance is adjustable from 6"- 30". Ideal for ADA applications, doors located in restrooms, industrial clean rooms or surgical areas. Includes a stainless steel face plate. Add suffix PLAIN to part number for no legend on face plate.	215
	• 216: IR Switch & 4 ½" Square Face Plate (Fits Single & 2-Gang Junction Boxes) • 216-L: IR Switch & 2 ¾" x 4 ½" Face Plate (Fits Single-Gang Box) • 216-N: IR Switch & 1 11/16" x 4 ½" Face Plate (Fits 1 ¾" Door Frame)	
216TX Series: Infrared Wireless "Touchless"		
	Wireless version of our 216 Active Infrared Switches. Activator distance adjustable from 1" to 5". Includes mounting box & transmitter. Four different face plate legends available.	295
	• 216TX-HG • 216TX-TG • 216TX-HT • 216TX-WT	
830 Series: Heavy Duty Keyswitches		
	Rugged Keyswitches with SPDT switch in a choice of either momentary contact or maintained contact. For ultimate durability, the integral lock cylinder cover provides a key "dead stop" and protects against wires becoming tangled in the locking mechanism. Includes a stainless steel face plate.	110
	• 830-A: Maintained Keyswitch & 4 ½" Square Face Plate • 830-B: Momentary Keyswitch & 4 ½" Square Face Plate (Fits Single & 2-Gang Boxes) • 830-AL: Maintained Keyswitch & 2 ¾" x 4 ½" Face Plate • 830-BL: Momentary Keyswitch & 2 ¾" x 4 ½" Face Plate (Fits Single-Gang Box) • 830-AN: Maintained Keyswitch 1 11/16" x 4 ½" Face Plate • 830-BN: Momentary Keyswitch 1 11/16" x 4 ½" Face Plate (Fits 1 ¾" Door Frame) • RG LED Option: Red and Green Indicator LED option, RCM included; add suffix -RG to part number: add \$30.00. • KEY-CYL: 1 1/8" Mortise cylinder with Adams-Rite cam sold separately; add \$50.00	
830 Series: Combination Keyswitches & Jamb Switches		
	Rugged 830 Series Keyswitch and 59J Series Jamb Switch are integrated onto a single 4 ½" square stainless steel back plate. Mounts to a 2-gang box electrical box.	185
	• 830A-59J-H: Maintained Keyswitch & 59J-H • 830B-59J-H: Momentary Keyswitch & 59J-H • 830A-59J-HSS: Maintained Keyswitch & 59J-HSS • 830B-59J-HSS: Momentary Keyswitch & 59J-HSS • 830A-59J-P: Maintained Keyswitch & 59J-P • 830B-59J-P: Momentary Keyswitch & 59J-P • 830A-59J-W: Maintained Keyswitch & 59J-W • 830B-59J-W: Momentary Keyswitch & 59J-W • 830A-59J-WSS: Maintained Keyswitch & 59J-WSS • 830B-59J-WSS: Momentary Keyswitch & 59J-WSS • 830A-59J-PLAIN: Maintained Keyswitch & 59J-PLAIN • 830B-59J-PLAIN: Momentary Keyswitch & 59J-PLAIN • RG LED Option: Red and Green Indicator LED option, RCM included; add suffix -RG to part number: add \$30.00. • KEY-CYL: 1 1/8" Mortise cylinder with Adams-Rite cam sold separately; add \$50.00	
US DOLLARS—OCTOBER 2018 Prices are subject to change without notice. PAGE 4		



RETAIL PRICE LIST 2018

PART #	DESCRIPTION	RETAIL PRICE
Sedco™ Door Activation Switch Products (continued)		
NexGen IR Hardwired Touchless Switches		
	The NexGen IR Touchless Series actuators use infrared sensing technology and microprocessor control to provide superior activation in a smaller size switch.	
	NG-IR-A - Hardwired Version NGS-IR-A - Wireless Version	175 225
NexGen CT Hardwired & Wireless Series Switches		
 	The NexGen CT Series actuators use capacitive touch technology to provide sensitive, reliable operation. Faceplate legends available: • NG-CT-HSS • NG-CT-P	
	NG-CT-HSS or NG-CT-P - Hardwired Versions NGS-CT-HSS or NGS-CT-P - Wireless Versions <i>Braille text option available. Add \$30</i>	175 225
Switch Accessories		
12024	24V AC transformer.	16
2WIRE Module	Module that will allow the connection of NexGen wired or 216 series switches using only two wires.	100
BRM Bridge Rectifier Module	Converts AC voltage to DC voltage. 100 V AC maximum.	25
E13-25JA	UL listed replacement SPDT micro-switch. Includes mounting nuts and spring.	12
DPDT Option	Double Pole Double Throw switch. <i>Add suffix DPDT to part number (example: 59-H-DPDT).</i>	13
E19-00J	UL listed DPDT micro-switch. Includes mounting nuts and spring.	25
614-1RBUT, 614-1ABUT (anodized), 614-1BBUT (black)	1" diameter SPST replacement piezo button switch only.	70
Face Plates	Replacement face plates for any standard switch. <i>Add suffix PO to part number (example: 59-H-PO).</i>	40
HDWE	Screw packs for mounting switches.	6
RCM Relay Conversion Module	Module that will allow a single input signal to operate two discrete outputs.	50
RIM Relay Isolation Module	Module for use where higher current may be used exceeding standard relay ratings (i.e. locks, alarms, etc.)	50
WR UPGRADE	Water resistant microswitch and wires. <i>Add suffix WR to part number.</i>	65
WR-KIT	Field installable water resistant microswitch and wires.	65
10001	Gasket compatible with 59 Series switches.	6
Switch Mounting Boxes		
All mounting boxes are exterior grade polycarbonate surface mounting boxes designed so the switch will recess mount for superior weather protection and to eliminate potential snagging.		
One Piece Mounting Boxes:		
1035 Universal Jamb Box	2" deep jamb box. Compatible with 59J Series switches and many other switches designed for jamb mount.	30
255-R	2-gang recessed mount box.	30
Two Piece Mounting Boxes: 2 Piece design makes battery replacement quick and easy for wireless applications.		
1015 High Profile Universal Square Box	Compatible with 59, 59V, 1078, 216, 830, & 614 series switches. <i>10001 gasket for additional weatherproofing; order separately: \$6.00</i>	30
US DOLLARS—OCTOBER 2018		Prices are subject to change without notice. PAGE 5

RETAIL PRICE LIST 2018

PART #	DESCRIPTION	RETAIL PRICE
ClearPath™ Turnkey Radio Control Packages for Low Energy Doors		
Turnkey packages come with all products assembled. Everything needed comes in a single carton. <i>Refer to pages 8-11 for individual product descriptions.</i>		
ClearPath™ Kits		
Kits listed below include -H face plates. For -HSS face plates, substitute HSS for H in the part number below, for -P face plates, substitute P for H.		
Package 59	CTP-H 2:59-H; 2:CP/TX; 1:CP/RX	305
Package 59R4	CTP-R4-H 2:59R4-H; 2:CP/TX-R4; 1:CP/RX	305
Package 59R6	CTP-R6-H 2:59R6-H; 2:CP/TX-R6; 1:CP/RX	330
Package 59J	CTP-J-H 2:59J-H; 2:CP/TX-J; 1:CP/RX	300
Vestibule Package 59	CTP-HV 2:59-H; 2:CP/STX; 1:59V-H; 1:CP/TX-V; 2:CP/RX	635
Vestibule Package 59J	CTP-J-HV 2:59J-H; 1:59V-H; 2:CP/STX-J; 1:CP/TX-V; 2:CP/RX	630
Dual-Switch ClearPath™ Kits—NEW!		
	Kits listed below include -H face plates. For -HSS face plates, substitute HSS for H in the part number below, for -P face plates, substitute P for H.	
	CTP2-H —4:59-H; 4:CP/TX; 1:CP/RX	543
	CTP2-R4-H —4:59R4-H; 4:CP/TX-R4; 1:CP/RX	543
	CTP2-R6-H —4:59R6-H; 4:CP/TX-R6; 1:CP/RX	591
ClearPath Spectrum™ 2.4 GHz Radio Control Products		
The next generation of our radio control products. The ClearPath Spectrum features a 2.4 GHz frequency that provides reliable wireless activation and versatile programming for automatic door activation.		
S-TRX; S-TRX-R4; S-TRX-R6: Wall Mount Transceivers		100
  	Complete with transceiver, wire harness and battery installed in a surface mounting box.	
	For 1015 surface box, specify S-TRX-1015 <i>Pictured with 59-H, 59R4-H & 59R6-H (sold separately).</i>	
S-TRX-J: Jamb Mount Transceiver		100
	Complete with transceiver, wire harness, and battery installed in a 1010 jamb surface mounting box.	
	<i>Pictured with 59J-H (sold separately)</i>	
S-TRX-V: Dual Transceivers		190
	Complete with 2 transceivers, wire harnesses, and batteries installed in a 1015 surface mounting box.	
	<i>Pictured with 59V-H (sold separately)</i>	
S-TRX-P: Post Transceiver		100
	Complete with transceiver, wire harness, and battery installed on a mounting platform that spans the top of the 608 Series Post assembly.	
US DOLLARS—OCTOBER 2018		Prices are subject to change without notice. PAGE 10



RETAIL PRICE LIST 2018

PART #	DESCRIPTION	RETAIL PRICE
ClearPath  Radio Control Products (continued)		
CP/TX-P: Post Transmitter	Complete with transmitter, wire harness and 9V battery installed on a mounting platform that spans the top of the 608 Series Post assembly.	70
CP/STX-P: Post Sequencing Transmitter	Vestibule sequencing version of the CP/TX-P. Sequence the opening of vestibule doors one after the other from either direction via 608 Series Posts.	95
CP/TX-VP: Post Dual Transmitter	Complete with 2 transmitters, wire harnesses and 9V batteries installed on a mounting platform that spans the top of the 608 Series Post assembly. Individually operate 2 doors in a vestibule when used in combination with the 608 Series Vestibule Posts.	130
CP/TX-HH1: Handheld Micro-Transmitter	 1-button micro-transmitter combines small overall size with a large easy to activate button. Small enough to wear on a neck chain (included).	75
CP/TX-HH2: Handheld Micro-Transmitter	 2-button micro-transmitter combines small overall size with 2 large easy to activate buttons. Small enough to wear on a neck chain (included).	80
ClearPath™ Multi-Mode Receivers	3 selectable frequencies: HDRC™, 300 MHz, 390 MHz plus ClearPath™ receivers are capable of being programmed to one of four different modes: Mode 1: Standard Receiver Mode 2: Receiver with adjustable time delay 0-20 seconds Mode 3: Dual Receiver Mode 4: Receiver with 2 sequenced outputs & delay 0-20 seconds Mode 5: Receiver with ratchet relay output	
CP/RX: Multi-Mode Receiver	 Compact Receiver: Includes Mode 1 & 2.	73
CP/RXM: Multi-Mode Receiver with Sequenced Output	 Compact Receiver: Includes Mode 1, 2, 3 & 4. RXM provides sequenced output which allows processes such as releasing a lock before activating an opener	115
CP/RXR: Multi-Mode Receiver with Ratcheting Relay	 Compact Receiver: Includes Mode 1, 2, & 5. RXR provides ratcheting relay which allows for a continuous output until a second activation signal is received.	83
RXM Module	Plug-in module kit to field activate Mode 3 & 4.	42
RXR Module	Plug-in module kit to activate Mode 5.	10

RETAIL PRICE LIST 2018

PART #	DESCRIPTION	RETAIL PRICE
1010	Compatible with 59J & 614-NSS Series switches	30
1020 Low Profile	Compatible with 59, 216, & 614 Series switches 10001 gasket for additional weatherproofing; order separately: \$6.00	30
1025	Round boxes compatible with all 59R4 Series switches	30
1030	Round boxes compatible with all 59R6 Series switches	30
Escutcheon Plates	 Attractive stainless steel plates that can be surface mounted directly to the wall or attached to a single-gang or 2-gang electrical box. • ESC-59R4: Plate for 59R4 Series Switches • ESC-59R6: Plate for 59R6 Series Switches	90 100
608, 628 and 514 Series Door Activator Switch Bollards w/LongLife™ Finishes Heavy duty construction. Each bollard is made from 1/8" thick tubular steel with a two-coat industrial grade exterior powder coated finish; these switch bollards are the most durable available.		
608 AND 628 BOLLARD ASSEMBLIES INCLUDES: 5" X 5" X 42" Bollard w/LongLife™ Finish, Rugged Polycarbonate Cap and ABS Plastic Rust Shield. Standard Steel “U” Shaped Mounting Shoe included for part number ending in 42. Surface external option features mounting plate welded to bottom of bollard to provide additional stability and easier installation. For Surface external option, change 42 to SE on part number, at no additional charge. In-Ground Mounting option features Steel “U” Shaped Mounting Shoe with 16” flange that extends into the ground, making the entire bollard assembly 58”. For In-Ground option, change 42 to 58 and add \$40.		
608 Blank Bollard Assembly Only	Customize in the field. Bollard has no cutout preps. • 608-GR-42: Gray Bollard Assy For alternate colors, change GR to BR (Dark Bronze), WH (White), or BL (Black): In-ground mounting shoe add \$40.00; Change Suffix 42 to 58	360
608-J Bollard Assembly with Switch Cutout	Add your own switch. Bollard is prepped with a 2-gang cutout (2 7/8" x 3 1/4"). • 608-J-GR-42: Gray Bollard Assy w/2-Gang Cutout For alternate colors, change GR to BR (Dark Bronze), WH (White), or BL (Black): In-ground mounting shoe add \$40.00; Change suffix 42 to 58	370
608-R Bollard Assembly with Recessed Switch Cutout	Add your own switch. Bollard is prepped with recessed switch cutout and mounting bracket (5" x 5" cutout). • 608-R-GR-42: Gray Bollard Assy w/2-Gang Cutout For alternate colors, change GR to BR (Dark Bronze), WH (White), or BL (Black): In-ground mounting shoe add \$40.00; Change suffix 42 to 58	380
608 Bollard Assembly with Recess Mounted Switch	 Includes everything needed. Bollard assembly with recess mounted 59 Series Switch installed. • 608-H-GR-42: Gray Bollard Assy, Recessed 59-H • 608-HSS-GR-42: Gray Bollard Assy, Recessed 59-HSS • 608-P-GR-42: Gray Bollard Assy, Recessed 59-P • 608-W-GR-42: Gray Bollard Assy, Recessed 59-W • 608-WSS-GR-42: Gray Bollard Assy, Recessed 59-WSS For alternate colors, change GR to BR (Dark Bronze), WH (White), or BL (Black), Surface External Option (Foot), Change Suffix 42 to SE. In-ground mounting shoe add \$40.00; Change suffix 42 to 58	450
608 Bollard Assembly with Wireless Recess Mounted Switch	 Complete wireless package. Bollard assembly with recess mounted 59 Series Switch installed, transmitter and mounting platform (CP/TX-P). • 608-HT-GR-42: Gray Bollard Assy, Recessed 59-H, CP/TX-P • 608-HSST-GR-42: Gray Bollard Assy, Recessed 59-HSS, CP/TX-P • 608-PT-GR-42: Gray Bollard Assy, Recessed 59-P, CP/TX-P • 608-WT-GR-42: Gray Bollard Assy, Recessed 59-W, CP/TX-P • 608-WSST-GR-42: Gray Bollard Assy, Recessed 59-WSS, CP/TX-P For alternate colors, change GR to BR (Dark Bronze), WH (White), or BL (Black), Surface External Option (Foot), Change Suffix 42 to SE. In-ground mounting shoe add \$40.00; Change suffix 42 to 58 Sequencing transmitter add \$20.00; Change T to S; ClearPath Spectrum, add \$30; Change T to -TRX (example: 608-H-TRX-GR-42)	525

RETAIL PRICE LIST 2018

PART #	DESCRIPTION	RETAIL PRICE
608, 628 and 514 Series Door Activator Switch Bollards w/LongLife™ Finishes (continued)		
608 Vestibule Bollard Assembly with 59V Vestibule Switch		525
	Includes everything needed to activate 2 doors. Bollard assembly with 59V Series Vestibule Switch. • 608-HV-GR-42: Gray Bollard Assy, 59V-H • 608-HSSV-GR-42: Gray Bollard Assy, 59V-HSS • 608-PV-GR-42: Gray Bollard Assy, 59V-P • 608-WV-GR-42: Gray Bollard Assy, 59V-W • 608-WSSV-GR-42: Gray Bollard Assy, 59V-WSS <i>For alternate colors, change GR to BR (Dark Bronze), WH (White), or BL (Black), Surface External Option (Foot), Change Suffix 42 to SE. In-ground Mounting Shoe Add \$40.00; Change 42 to 58</i>	
608 Vestibule Bollard Assembly with WIRELESS 59V Vestibule Switch		675
	Complete wireless package to activate 2 doors. Bollard assembly with 59V Series Vestibule Switch, 2 transmitters and mounting platform (CP/TX-VP). • 608-HTV-GR-42: Gray Bollard Assy, 59V-H, CP/TX-VP • 608-HSSTV-GR-42: Gray Bollard Assy, 59V-HSS, CP/TX-VP • 608-PTV-GR-42: Gray Bollard Assy, 59V-P, CP/TX-VP • 608-WTV-GR-42: Gray Bollard Assy, 59V-W, CP/TX-VP • 608-WSSTV-GR-42: Gray Bollard Assy, 59V-WSS, CP/TX-VP <i>For alternate colors, change GR to BR (Dark Bronze), WH (White), or BL (Black), Surface External Option (Foot), Change Suffix 42 to SE, In-ground Mounting Shoe Add \$40.00; Change 42 to 58</i> <i>ClearPath Spectrum S-TRX-VP, add \$60; Change TV to V-TRX (example: 608-HV-TRX-GR-42)</i>	
628 Dual-Switch Bollards		
	Dual Switch bollards feature all the benefits of the 608 bollard: rugged 1/8” thick tubular steel construction, LongLife™ finish and a rust shield. (gray finishes and 59-H switches listed below. For dark bronze finish, substitute BR for GR. For 59-HSS or 59-P, substitute HSS or P for H). • 628-H-GR-42: 42” Bollard Assy w/two recessed 59-H switches, surface mounting • 628-H-GR-58: 58” Bollard Assy w/two recessed 59-H switches, in ground mounting • 628-H-GR-SE: Bollard Assy w/two recessed 59-H switches, surface external mounting • 628-HT-GR-42: 42” Bollard Assy w/two recessed 59-H switches, transmitter, surface mounting • 628-HT-GR-58: 58” Bollard Assy w/two recessed 59-H switches, transmitter, in ground mounting • 628-HT-GR-SE: Bollard Assy w/two recessed 59-H switches, transmitter, surface external mounting	600 640 600 675 715 675
514 BOLLARD ASSEMBLY INCLUDES: 2" X 2"X 42" Bollard w/LongLife™ Finish, Welded Top Piece, Steel "U" Shaped Surface Mounting Shoe and ABS Plastic Rust Shield.		
514 Blank Bollard Assembly Only		245
Customize in the field. Bollard is prepped for wiring. • 514-GR-SE: Gray Bollard Assy OR • 514-BR-SE: Dark Bronze Bollard Assy		
514 Bollard Assembly with 59J Series Jamb Switch		335
	Includes everything needed. Bollard assembly with 59J Series Switch installed. • 514-H-GR-SE: Gray Bollard Assy, 59J-H, 1010 • 514-HSS-GR-SE: Gray Bollard Assy, 59J-HSS, 1010 • 514-P-GR-SE: Gray Bollard Assy, 59J-P, 1010 • 514-W-GR-SE: Gray Bollard Assy, 59J-W, 1010 • 514-WSS-GR-SE: Gray Bollard Assy, 59J-WSS, 1010 <i>Dark Bronze Color; Change GR to BR</i>	
514 Bollard Assembly with WIRELESS Switch		375
	Complete wireless package. Bollard assembly with recess mounted 59J Series Switch installed, transmitter and mounting platform (CP/TX-J). • 514-HT-GR-SE: Gray Bollard Assy, 59J-H, CP/TX-J • 514-HSST-GR-SE: Gray Bollard Assy, 59J-HSS, CP/TX-J • 514-PT-GR-SE: Gray Bollard Assy, 59J-P, CP/TX-J • 514-WT-GR-SE: Gray Bollard Assy, 59J-W, CP/TX-J • 514-WSST-GR-SE: Gray Bollard Assy, 59J-WSS, CP/TX-J <i>Dark Bronze Color; Change GR to BR, Sequencing transmitter add \$20.00; Change T to S</i> <i>S-TRX-J add \$30; Change T to -TRX</i>	

RETAIL PRICE LIST 2018

PART #	DESCRIPTION	RETAIL PRICE
Bollard Accessories		
608-CAP	Replacement black polycarbonate bollard cap.	50
6082-SHOE	Surface mounting shoe & installation hardware. <i>Please specify color to ensure matching hardware-GR,BR, BL or WH</i>	50
6083-SHOE	In-ground mounting shoe and installation hardware. <i>Please specify color to ensure matching hardware-GR,BR, BL or WH</i>	90
ClearPath™ Radio Control Products		
<i>Universal radio control products. All products feature selectable frequencies: HDRC™, 300 MHz and 390 MHz. ClearPath™ provides the most reliable wireless activation of automatic doors.</i>		
ClearPath™ Transmitters		
All transmitters feature SignalLock™ that will guarantee the radio signal is transmitted every time a switch is activated.		
CP/TX (59); CP/TX-R4 (59R4); CP/TX-R6 (59R6): Wall Mount Transmitters		70
	Complete with transmitter, integrated signal enhancing antennas, wire harness and 9V battery installed in a surface mounting box. For 1015 surface box, specify CP/TX-1015 <i>Pictured with 59-HSS, 59R4-HSS & 59R6-HSS (sold separately).</i>	
CP/STX (59); CP/STX-R4 (59R4); CP/STX-R6 (59R6): Vestibule Sequencing Transmitters		95
	Vestibule sequencing version of the CP/TX. Sequence the opening of vestibule doors one after the other from either direction. For 1015 surface box, specify CP/STX-1015 <i>Pictured with 59-HSS, 59R4-HSS & 59R6-HSS (sold separately).</i>	
CP/TX-J: Jamb Mount Transmitter		70
	Complete with transmitter, wire harness and 9V battery installed in the 1010 jamb surface mounting box. <i>Pictured with 59J-H (sold separately).</i>	
CP/STX-J: Vestibule Sequencing Transmitter		95
	Vestibule sequencing version of the CP/TX-J. Sequence the opening of vestibule doors one after the other from either direction. <i>Pictured with 59J-H (sold separately).</i>	
CP/TX-V: Dual Transmitters		130
	Complete with 2 transmitters, wire harnesses and 9V batteries installed in the 1015 surface mounting box. Individually operate 2 doors in a vestibule when used in combination with the 59V Vestibule Series Switches. <i>Pictured with 59V-H (sold separately).</i>	